

81. During T_r the velocity v_0 is constant (in the direction we choose as $+x$) and obeys $v_0 = D_r/T_r$ where we note that in SI units the velocity is $v_0 = 200(1000/3600) = 55.6$ m/s. During T_b the acceleration is opposite to the direction of v_0 (hence, for us, $a < 0$) until the car is stopped ($v = 0$).

- (a) Using Eq. 2-16 (with $\Delta x_b = 170$ m) we find

$$v^2 = v_0^2 + 2a\Delta x_b \implies a = -\frac{v_0^2}{2\Delta x_b}$$

which yields $|a| = 9.08$ m/s².

- (b) We express this as a multiple of g by setting up a ratio:

$$a = \left(\frac{9.08}{9.8} \right) g = 0.926g .$$

- (c) We use Eq. 2-17 to obtain the braking time:

$$\Delta x_b = \frac{1}{2} (v_0 + v) T_b \implies T_b = \frac{2(170)}{55.6} = 6.12 \text{ s} .$$

- (d) We express our result for T_b as a multiple of the reaction time T_r by setting up a ratio:

$$T_b = \left(\frac{6.12}{400 \times 10^{-3}} \right) T_r = 15.3T_r .$$

- (e) We are only asked what the *increase* in distance D is, due to $\Delta T_r = 0.100$ s, so we simply have

$$\Delta D = v_0 \Delta T_r = (55.6)(0.100) = 5.56 \text{ m} .$$